

785nm Laser Diode

Description

The IDP785DBR Series of high-power edge-emitting lasers are based on Idealphotonics's advanced single-frequency laser technology. It provides a diffraction limited, single lateral and longitudinal mode beam. Facets are passivated for high-power reliability. Applications for the 785 nm laser diode include Raman spectroscopy and optical storage.

Feature

Available in several package styles

Pulsed operation for spectral stability at short pulse lengths

High power for CW applications

High Slope Efficiency

Technology

DBR Single-Frequency Laser Chip

AlGaAs QW Active Layer

Epi designed for high reliability

Specification

Absolute Maximum Rating

Parameter	Symbol	Unit	Min	Max
Storage Temperature	T _{STG}	°C	0	80
Operating Temperature	T _{OP}	°C	5.0	70
CW Laser Forward Current, T=25°C	I _F	mA	-	150**
Pulsed Laser Forward Current, T=25°C, PW=300 ns, DC=10%	I _F	A	-	0.3
Laser Reverse Voltage	V _R	V	-	0.0
Photodiode Forward Current <u>1</u> /	I _P	mA	-	5.0
Photodiode Reverse Voltage <u>1</u> /	V _R	V	-	20.0
Photodiode Dark Current, V _R =10V, LD I _F =0, <u>1</u> /	I _D	nA	-	50
TEC Current <u>1</u> /	I _{TEC}	A	-2.0	2.0
TEC Voltage <u>1</u> /	V _{TEC}	V	-6.0	6.0
Thermistor Current <u>1</u> /	I _{THRM}	mA	-	1.0

Thermistor Voltage <u>1/</u>	V_{THRM}	V	-	10
External Back Reflection	-	dB	-	-14
Lead Soldering Temperature, 10 sec. Max.	-	°C	-	260

1/ Butterfly package 2/ TO8 package**Do not exceed drive current or operating power of supplied LIV

CW Characteristics at TC = 25°C unless otherwise specified

Parameter	Symbol	Unit	Min	Typ	Max
Center Wavelength @ 150mA	λ_c	nm	783	785	787
Optical Output Power @ 150mA	P_o	mW	See Power Options Call-out		
Slope Efficiency, <u>1/</u>	η_d	W/A	0.3	0.36	
Slope Efficiency	η_d	W/A	0.6	0.75	-
Threshold Current	I_{th}	mA	-	50	70
Laser Series Resistance	R_s	Ω	-	2.0	2.5
Laser Forward Voltage @ 150mA	V_F	V	-	2.0	2.5
Thermistor Resistance @ 25°C, <u>2/</u>	R_T	K Ω	-	10	-
Photodiode Dark Current, $V_R=10V$, LD $I_F=0$, <u>2/</u>	I_D	nA	-	-	50
Laser Line Width @ 150mA	$\Delta\nu$	MHz	-	3	10
Polarization Extinction Ratio, <u>1/</u>	PER	dB	-16	-19	-
Beam Divergence @ FWHM	$\theta \times \theta_{\perp}$	°	-	6 X 32	8 X 34
Side Mode Suppression Ratio	SMSR	dB	-30	-	-
Laser Polarization				TE	
Mode Structure			Fundamental Mode		

1/ Butterfly package 2/ TO-8 package

Handling Precautions

These devices are sensitive to ESD. When handling the module, grounded work area and wrist strap must be used. Always store in an antistatic container with all leads shorted together.

Package

T08	Butterfly
 A photograph of a T08 package, which is a small, cylindrical, gold-colored component with a central lens and several pins extending from the bottom. It is set against a dark blue background with light rays emanating from it.	 A photograph of a Butterfly package, which is a rectangular, gold-colored component with multiple pins on one side and a fiber optic cable attached to the other. It is set against a dark blue background with light rays emanating from it.