

## 920 nm Laser Diode

### Description

The IDP920DBR Series of high-power edge-emitting lasers are based on Idealphotonics's advanced single-frequency laser technology. It provides a diffraction limited, single lateral and longitudinal mode beam. Facets are passivated for high-power reliability. Applications for the 920 nm laser diode include spectroscopy, difference frequency generation, and low power DPSS replacement. It can be ordered to a specific wavelength target for frequency doubling to specific trapping wavelengths.

### Feature

- WAvaliable in several package styles
- Pulsed operation for spectral stability at short pulse lengths
- High power for CW applications
- High Slope Efficiency

### Technology

- DBR Single-Frequency Laser Chip
- AlGaAs QW Active Layer
- Epi designed for high reliability

### Specification

#### Absolute Maximum Rating

Parameter	Symbol	Unit	Min	Max
Storage Temperature	T <sub>STG</sub>	°C	0	80
Operating Temperature	T <sub>OP</sub>	°C	5.0	70
CW Laser Forward Current, T=T <sub>op</sub>	I <sub>F</sub>	mA	-	150**
Pulsed Laser Forward Current, T=25°C, PW=300 ns, DC=10%	I <sub>F</sub>	A	-	0.5
Laser Reverse Voltage	V <sub>R</sub>	V	-	2.0
Photodiode Forward Current 1/ 2/	I <sub>P</sub>	mA	-	5.0
Photodiode Reverse Voltage 1/ 2/	V <sub>R</sub>	V	-	20.0
Photodiode Dark Current, V <sub>R</sub> =10V, LD I <sub>F</sub> =0, 1/ 2/	I <sub>D</sub>	nA	-	50
TEC Current 1/ 2/	I <sub>TEC</sub>	A	-2.5	2.5

TEC Voltage 1/ 2/	$V_{TEC}$	V	-6.0	6.0
Thermistor Current 1/ 2/	$I_{THRM}$	mA	-	1.0
Thermistor Voltage 1/ 2/	$V_{THRM}$	V	-	10
ESD (HBM)	-	V	-	500
External Back Reflection	-	dB	-	-14
Lead Soldering Temperature, 10 sec. Max., 1/ 2/	-	°C	-	260
Fiber Pull Force 1/	-	N	-	5.0
Fiber Bend Radius 1/	-	mm	-	35

1/ Butterfly package 2/ TO8 package\*\*Do not exceed drive current or operating power of supplied LIV

CW Characteristics at  $TC = 25^{\circ}C$  unless otherwise specified

Parameter	Symbol	Unit	Min	Typ	Max
Center Wavelength	$\lambda_c$	nm	918	920	922
Optical Output Power @ LIV current	$P_o$	mW	40-120		
Slope Efficiency, 1/	$\eta_d$	W/A	0.3	0.36	-
Slope Efficiency	$\eta_d$	W/A	0.6	0.72	-
Threshold Current	$I_{th}$	mA	-	30	40
Laser Series Resistance	$R_s$	$\Omega$	-	2.0	2.5
Laser Forward Voltage	$V_F$	V	-	2.0	2.5
Thermistor Resistance $25^{\circ}C$ , 1/ 2/	$R_T$	$k\Omega$	-	10	-
Photodiode Dark Current, $V_R=10V$ ,LD $I_F=0$ , 1/ 2/	$I_D$	nA	-	-	50
Laser Line Width	$\Delta v$	MHz	-	8	10
Beam Divergence @ FWHM	$\theta \times \theta_{\perp}$	°	-	6 X 32	8 X 34
Side Mode Suppression Ratio	SMSR	dB	-30	-	-
Polarization Extinction Ratio, 1/	PER	dB	-16	-19	-
Laser Polarization				TE	
Mode Structure			Fundamental Mode		

1/ Butterfly package 2/ TO-8 package

## Handling Precautions

These devices are sensitive to ESD. When handling the module, grounded work area and wrist strap must be used. Always store in an antistatic container with all leads shorted together.

## Package

TO8	Butterfly
	